LAVORO
ENGINEERING LIFE

TECHNICAL INFORMATION

**ELITE** 1671.02
**TECH RANGE (FOREST)**

EN ISO 17249:2013/AC:2014
EN ISO 20345:2011 CE
S3 HI CI HRO SRC

**SIZES** EU 39 - 48
UK 6 - 13
MP 247 - 315

CHAINSAW PROTECTION CLASS 2

CHAINSAW PROTECTION

WATERPROOF LINNING

sympatex®

CRAZY HORSE LEATHER

CLIMA CORK SYSTEM

TEMPERATURE AND HUMIDITY REGULATOR

EXTRA PROTECTION

DIRECT INJECTED PU + RUBBER












## CHARACTERISTICS

| | |
|---|---|
| **SOLE** | DIRECT INJECTED PU + RUBBER |
| **PROTECTIVE TOE CAP** | STEEL (Impact-resistant up to 200J) |
| **PROTECTIVE MIDSOLE** | STEEL (perforation-resistant up to 1100 N) |
| **UPPER MATERIAL** | CRAZY HORSE LEATHER - BROWN |
| **LINNING MATERIAL** | WATERPROOF MEMBRANE SYMPATEX |
| **INSOLE** | LAVORO CHROMIUM FREE |
| **WIDTH** | 11 |

CHAINSAW PROTECTION · RESISTANT UP TO 300°C · ANTISTATIC · sympatex® · CLIMA CORK SYSTEM · WATER REPELLENT UPPER · ANTI-SLIP SOLE

In the interest of product development Lavoro reserves the right to change or amend the specifications of the products, without previous notice.