



art & science of
amazing protection



Data Sheet

BLACK NITRILE



POWDER FREE
EXAMINATION
GLOVES

Features

Low extractable particulate level

Manufactured powder-free to avoid exposure to allergens and skin irritants

Finger textured

Strategically placed finger textured surfaces increase grip to reduce gripping effort needed, ultimately reducing hand strain.

Ambidextrous

Fits either hand conveniently without needing to determine left or right, for simpler donning.

Enhanced comfort & fit

Soft and conforming fit provides increased dexterity allowing for prolonged wear.

Professional black colour

Sleek black glove colour reduces visible stains to maintain a professional appearance.

Application

ASAP Black Nitrile gloves are recommended to be used in industries for

- Protection from bodily fluids such as blood or mucus.
- Tattoo parlours—Black colour does not easily show blood.
- Procedures that require increased tactile sensitivity.
- Increased protection with overall great comfort for industries such as Beauty, Food processing, Cleaning, etc.

Industry icons:



Examination & Surgery (E&S)



Research & Development (R&D)



Building & Construction (B&C)

Regulations

- Medical Device Regulation (EU) 2017/745
- PPE Regulation (EU) 2016/425
- Food contact Regulation (EU) 1935/2004

Harmonised Standards

- | | |
|-----------------|-------------------------|
| • EN 455-1:2020 | • EN ISO 21420:2020 |
| • EN 455-2:2015 | • EN 374-1:2016+A1:2018 |
| • EN 455-3:2015 | • EN 374-4:2019 |
| • EN 455-4:2009 | • EN 374-5:2016 |

Quality Assurance

- ISO 9001:2015
- ISO 13485:2016
- ISO 14001:2015



Physical Properties Sheet: Product Information

Series Number	20530
Acceptable Quality Level (AQL)	1.5
Packaging	100 pcs per box, 10 boxes per carton

Packaging Dimensions

Inner	235 x 127 x 60mm
Carton	315 x 260 x 245mm



Product Size Codes

Small	Medium	Large
S 7	M 8	L 9
20532	20533	20534

Physical Properties Specification: Dimension Specification

	Specification Type		Specification	Test Method
Dimensions	Palm Width	Small	85 ± 5mm	EN 455-2
		Medium	95 ± 5mm	
		Large	105 ± 5mm	
	Length		Min 240mm	
	Thickness (Single Wall)	Cuff (25mm from bead)	0.06 ± 0.01mm	
		Palm (centre of palm)	0.07 ± 0.02mm	
		Finger (13mm from tip)	0.10 ± 0.02mm	
Physical Properties	Force at break (N)	Before Aging	Min. 6.0N	EN 455-2
		After Aging	Min. 6.0N	
Physical Appearance	Rolled beaded cuff			
	Black Colour			
	Finger Textured Surface			
	Ambidextrous			

ASAP INTERNATIONAL SDN BHD

No. 1, Jalan Sitar 33/6, Seksyen 33,
40400 Shah Alam, Selangor,
Malaysia.

T : +603 5191 0166

E : info@whyasap.com

W : www.whyasap.com

ASAP INNOVATIONS LTD

Unit 7, Fonthill Business Park, The
Courtyard, Fonthill Rd, Ballyowen,
Dublin, D22 XA07, Ireland

T : +353 1 4661660

E : info@whyasap.ie

W : www.whyasap.ie

ASAP INNOVATIONS UK LTD

13, Diamond Court, Opal Drive,
Fox Milne, Milton Keynes,
MK15 0DU, United Kingdom

T : +44 (0)1908 909146

E : info@whyasap.co.uk

W : www.whyasap.co.uk